


Basic Network Protocol for Edge Devices **PNP2**

Ver.1.24e



Probe Inc.

29 December 2011

Orders

Document History	5
1. Overview.....	6
1-1. Description for PNP2 (Probe Network Protocol –second version).....	6
1-1-1. PNP2.....	6
1-1-2. the sort of Product line.....	6
1-2. Connection to the PNP2 device (Camera).....	7
1-2-1. Connecting PNP2.....	7
1-3. Protocol Structure.....	8
1-3-1. Term definition used in Protocol Message.....	8
1-3-2. Protocol Structures	9
2-1. Connection Command.....	11
2-1-1. [CNS]	11
2-1-2. [LGN],[LGS],[LGW]	11
2-1-4. [STA].....	12
2-2. Common Command	13
2-2-1. [RSU]	13
2-2-2. [RUC].....	13
2-2-3. [RSD]	13
2-2-4. [NVS]	15
2-2-5. [SDM, RSM].....	16
2-2-6. [RMT].....	17
2-2-7. [PTZ], [SCF]	18
2-2-8. [FSR].....	28
2-2-9. [FSP].....	29
2-2-10. [AGN].....	30
2-3. Firmware Upload & Update	31
2-3-1 [FUP, FUR].....	31
2-3-2 [FUS].....	32
2-4. Usage Reference	35
2-4-1. Relay setting setup	35
2-4-2. Alarm Input Setting	35
3. Video Server Protocol.....	35
3-1. Connection Command.....	36

3-1-1. [CNS]	36
3-1-2. [LGN]	36
3-1-3. [LGS], [LGW]	37
3-1-4. [STA].....	37
3-2. Transmitting Stream Data.....	38
4. Audio Receive Server Protocol (Audio from Microphone in Client)	40
4-1. Connection Command.....	40
4-1-1. [CNS]	40
4-1-2. [LGN]	40
4-1-3. [LGS], [LGW]	41
4-1-4. [STA].....	41
4-2. Receiving Stream Data	42
5. Audio Transmit Server Protocol (Audio from MIC in PNP2/Camera)	43
5-1. Connection Command.....	43
5-1-1. [CNS]	43
5-1-2. [LGN]	43
5-1-3. [LGS], [LGW]	44
5-2. Transmit Stream Data	44
Appendix #1 details of Motion Area information.....	46

Document History

Date	Note	Author	Revision
2010-09-14	-Initial Version	Lee Sang Min	1.0.0
2010-10-09	-Updated with "FPS" (Encoder Setup) Command	Kim Myeong Seong	1.0.1
2010-10-11	- Updated with "RSD" Command Structure	Lee Sang Min	1.0.2
2010-10-16	-Updated with "FSR", "FPS" commands.	Lee Sang Min	1.0.3
2010-11-1	-Updated the Resolution Byte of RSD command	Lee Sang Min	1.0.4
2010-11-18	- Added the speed setting in PTZ direction key	Lee Sang Min	1.0.5
2010-11-19	-Updated with FSP Parameter	Lee Sang Min	1.0.6
2010-11-23	-Updated with FUP, FUR,FUS Parameter -Updated with LGS, LGW	Lee Sang Min	1.0.7
2010-11-30	- Added with FUP Status (610~690)	Lee Sang Min	1.0.8
2011-01-13	-Updated the figure in "2.3 Firmware Upload & Update 2"	Lee Sang Min	1.0.9
2011-01-17	-Added the semi-auto in PTZ Focus Mode	Lee Sang Min	1.1.0
2011-01-31	-Updated in the connection flow	Lee Sang Min	1.1.2
2011-02-01	-Described the use of Motion Area Map -Resolution Value correction	Lee Sang Min	1.1.3
2011-03-11	-Remove unused command (RST, STM, SDC, SDS, RSS) -Update in Audio (Receive, Transmit) -Add the interval check time in "STA" -Add AGN Command -Update FSR.	Lee Sang Min	1.1.4
2011-03-14	-Remove all unused command and setting	Alex Oh	1.1.5
2011-04-25	-Add the additional function of PTZ	Lee Jung Min	1.1.6
2011-05-30	-Add new Op code of PTZ (Advanced Zoom) since firmware version 0.9.23_20110530 (PTI-H2100) since firmware version 0.9.67_20110530 (PMI-H2000/PMI-H2000s)	Lee Jung Min	1.1.7
2011-07-05	-Modify incorrect sample codes	Ko Sung Jin	1.1.8
2011-08-04	-Modify incorrected "FSR" Parameter	Ko Sung Jin	1.1.9
2011-11-17	-Modify incorrected audio protocols	Ko Sung Jin	1.2.0
2011-11-21	-Modify incorrected "NVS" parameter size	Ko Sung Jin	1.2.1.
2011-12-14	-Modify Audio transmit server protocol -Details of Motion detection message	Ko Sung Jin	1.2.2
2011-12-15	-Add the details of Motion Area information	Ko Sung Jin	1.2.3


2011-12-29	-Add new audio codec type (4-2)	Ko Sung Jin	1.2.4
------------	---------------------------------	-------------	-------

1. Overview

1-1. Description for PNP2 (Probe Network Protocol –second version)

1-1-1. PNP2

- To receive the video and audio stream, the Viewer application needs to connect to the Edge device equipped with PNP2. PNP2 is 2nd generation of probe-designed protocol and all IP-product in PROBE follows this protocol specification. In this manual, TCP/IP based streaming protocol will be explained even though there are more streaming protocol such as UDP, RTP and etc.



*PNP2: Interoperability protocol newly defined by PROBE camera (version of H.264) : Based-platform: TI DM365

*PNP1: Previous Interoperability protocol defined and used by PROBE Camera: Based-Platform: PENTA MICRO

*Viewer Application: External Software or Application connected to PROBE camera. It can be CMS (Central Management Software) or VMS (Video Management Software) or NVR (Network Video Recording) SW.

1-1-2. the sort of Product line

- Fundamentally, one PROBE SDK can be applicable all the IP products but there are small difference in the group of products with different parameter setting. To make it be clear with clarification. Below we are listing the group of sort according to the models which should be checked during the integration.

Group of Model	Product Model	Description
HD-1	PMI-H2000 PMI-H2000s PTI-H2100	High-definition PTZ
SD-1	PMI-400	Mini-PTZ with x10
SD-2	PTI-400~403 PTI-500~503	High-zoom PTZ with x33~39

*HD: High-Definition, SD: Standard-Definition

*Note: this definition of Group of Model will be referred in following section to differentiated setting respectively.



1-2. Connection to the PNP2 device (Camera)

1-2-1. Connecting PNP2

- There are 5 sorts of server in PNP2 protocol with different port i.e. (1.Control, 2.Video, 3.Audio Transmit, 4.Audio Receive, 5.Web Server.)


➤ A Windows application doesn't need to use the Web server among 5 servers. Accordingly, 4 servers (control, video, audio transmit and audio receive) are used in our SDK. A random number (*authorization number assigned by Servers*) is obtained after connecting each server.

➤ This authorization number is used as key for further connections such as user Authentication, Video, Audio.



- ✓ Control Server (Port) can be connected only if the connection request is succeed with 'LGS' (=Authentication success).

- ✓ Video and Audio Server (Port) can be connected only if respond will be 'LGS' (=Authentication success)
 - ✓ Audio Receive Port(Microphone use from SW Client) case is same flow with "Audio Transmit Port"
- Connection status between servers in camera (PNP2) and Viewer (=External Application) can be checked by the "STA" message every 5sec.



- If detected any disconnection from any servers in Camera, it is highly recommended to disconnect all servers and restart the connection from the beginning to get the key.

1-3. Protocol Structure

1-3-1. Term definition used in Protocol Message

Name	Term	Size(Byte)	Description
Start Code	SC	5	Packet Starting code ("STRT")
Packet Size	PS	4	Size in byte (CTR+CMD +PARAM DATA)
Control Byte	CTR	1	Determine: Stream and Control Data 0: Control Data 1: Stream Data
Command	CMD	4	Command Code
Parameters	PARAM DATA	Var.	Parameters for Command
Stream data	STREAM DATA	Var.	Stream Data
End Code	EC	5	Packet Ending Code ("END")

1-3-2. Protocol Structures

■ Control Server Protocol

SC	PS	CMD	PARAM DATA	EC
-----------	-----------	------------	-------------------	-----------

■ Video Server Protocol

* Data Transfer from Client to Server

SC	PS	CTR	STREAM DATA	EC
-----------	-----------	------------	--------------------	-----------

* Data Transfer from Server to Client

- Control data (CTR = 0)

SC	PS	CTR	CMD	PARAM DATA	EC
-----------	-----------	------------	------------	-------------------	-----------

- Stream data (CTR = 1)

SC	PS	CTR	STREAM DATA	EC
-----------	-----------	------------	--------------------	-----------

★ When data transfer from Server to Client, a control byte (CTR) is added to determine whether data is Stream or Control.

■ Audio Transmit Server Protocol

* Data Transfer from Client to Server

SC	PS	CTR	CMD	PARAM DATA	EC
-----------	-----------	------------	------------	-------------------	-----------

* Data Transfer from Server to Client

- Control data (CTR = 0)

SC	PS	CTR	CMD	PARAM DATA	EC
-----------	-----------	------------	------------	-------------------	-----------

- Stream data (CTR = 1)

SC	PS	CTR	STREAM DATA	EC
-----------	-----------	------------	--------------------	-----------

■ Audio Receive server protocol

* Data Transfer from Client to Server

- Control data (CTR = 0)

SC	PS	CTR	CMD	PARAM DATA	EC
-----------	-----------	------------	------------	-------------------	-----------

- Stream data (CTR = 1)

SC	PS	CTR	STREAM DATA	EC
-----------	-----------	------------	--------------------	-----------

* Data Transfer from Server to Client

- Control data (CTR = 0)

SC	PS	CTR	CMD	PARAM DATA	EC
----	----	-----	-----	------------	----

➤ **Usage**

1." PACKET SIZE" and "COMMAND" is composed with ASCII character.

Example #1) COMMAND "LGN" stands for the login

#2) In "PACK SIZE:0012" stands for the length of 18 byte

2. In the case when "PACKET SIZE" includes "CRT bit", then it represents the size from CTR-CMS-PARAM DATA, otherwise it does for the size of CMD-PARAM DATA only.


➤ **Clarification**

Response in the Command/Message: "Response" can be initialized by Server (=PNP2) even there is no "Request" from external viewer. This case is when there is the first connection request from viewer during login process. Server sends the defined responding once login is authorized. This is reason why there is command/message which is defined with only "Response" from chapter 2 below.

Notify in the Command/Message: "Notify" stands for the periodic update from Server (PNP2) even there is no certain request from viewer side. It can be kind of information like Time or connection status.

2. Control Server Protocol

The protocol for Control Server



2-1. Connection Command

2-1-1. [CNS]

Command Definition: Response to Connection Request from client

- Request (Client -> Server) to connect to the server
- Response (Server -> Client) for the Connection Request

"STRT"	P.S	"CNS"	RANDOM CONST	"_END"
--------	-----	-------	--------------	--------

➤ 'CNS' message is required before User Authentication

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'C'	'N'	'S'	0	RANDOM CONST (4Byte)
'_'	'E'	'N'	'D'	0									

- Notify (Server -> Client)

➤ is not used in this command

- Notify Response (Client -> Server) for the Notify.

➤ is not used in this command

2-1-2. [LGN],[LGS],[LGW]

Command Definition: User Authentication (Request)

- Request

"STRT"	P.S	"LGN"	RANDOM CONST	USER ID + PW	"_END"
--------	-----	-------	--------------	--------------	--------

➤ ID: 20byte,

➤ PW: 20byte

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'2'	'C'	'L'	'G'	'N'	0	RANDOM CONST (4Byte)
ID (20byte)							Password (20byte)						
'_'	'E'	'N'	'D'	0									

■ Response

"STR"	P.S	"LGS"	NULL	"_END"
-------	-----	-------	------	--------

➤ Authentication Success Message

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'L'	'G'	'S'	0	'_'	'E'	'N'	'D'	0
"STR"				P.S	"LGW"				NULL				"_END"				

➤ Authentication Failure Message

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'L'	'G'	'W'	0	'_'	'E'	'N'	'D'	0
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	---	-----	-----	-----	-----	---

■ Notify

➤ is not used in this command

■ Notify Response

➤ is not used in this command

2-1-4. [STA]

Command Definition: Connection status (check) message.

■ Request

➤ is not used in this command

■ Response

➤ is not used in this command

■ Notify

"STR"	P.S	"STA"	NULL	"_END"
-------	-----	-------	------	--------

➤ Check message for the connection status (every 5 seconds)

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'S'	'T'	'S'	0	'_'	'E'	'N'	'D'	0
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	---	-----	-----	-----	-----	---

■ Notify Response

"STR"	P.S	"STA"	NULL	"_END"
-------	-----	-------	------	--------

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'0'	'S'	'T'	'A'	'_'	'E'	'N'	'D'	0
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---

2-2. Common Command

2-2-1. [RSU]

Command Definition: User Type define (Response)

- Request
 - is not used in this command
- Response

"STRT"	P.S	"RSU"	PARAMETER	"_END"
--------	-----	-------	-----------	--------

➢ None(0), Administrator(1), Guest(2)

➢ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'5'	'R'	'S'	'U'	0	Param (1Byte)
'_'	'E'	'N'	'D'	0									

- Notify
 - is not used in this command
- Notify Response
- is not used in this command

2-2-2. [RUC]

Command Definition: Number of user connected now

- Request
 - is not used in this command
- Response

"STRT"	P.S	"RUC"	PARAM	"_END"
--------	-----	-------	-------	--------

➢ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'5'	'R'	'U'	'C'	0	Param (1Byte)
'_'	'E'	'N'	'D'	0									

- Notify
 - is not used in this command
- Notify Response
- is not used in this command

2-2-3. [RSD]

Command Definition : Stream Channel Setup

■ Request

“STRT”	P.S	“RSD”	PARAM	“_END”
---------------	------------	--------------	--------------	---------------

➤ Parameter = Channel Number (2Byte Integer)

➤ Sample Code (Unit : Byte)

‘S’	‘T’	‘R’	‘T’	0	‘0’	‘0’	‘0’	‘7’	‘R’	‘S’	‘D’	0	Channel(1Byte)	0
‘_’	‘E’	‘N’	‘D’	0										

■ Response

“STRT”	P.S	“RSD”	PARAM	“_END”
---------------	------------	--------------	--------------	---------------

➤ Parameter = (OP CODE + DATA)

➤ Sample Code (Unit : Byte)

‘S’	‘T’	‘R’	‘T’	0	‘0’	‘0’	‘2’	‘0’	‘R’	‘S’	‘D’	0	Param (46Byte)
‘_’	‘E’	‘N’	‘D’	0									

➤ Structure of Parameter (Unit: byte)

1	1	2	1	1	1	1	1	1	1	1	1	16	18
A	B	C	D	E	F	G	H	I	J	K	L	M	

MSB

LSB

Para	Description		Range																				
A	Streaming Channel		0~4																				
B	Video Type (0:NTSC, 1:PAL)		0/1																				
C	CBR value																						
D	<table border="1" style="width: 100%; height: 30px; margin-bottom: 5px;"> <tr> <td style="width: 50%;">Video type(2bit)</td> <td style="width: 50%;">Resolution (6bit)</td> </tr> </table> - Video Type (1:NTSC, 2:PAL) -Resolution <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 10%;">8</td><td style="width: 90%;">1080p (1920 x 1080)</td></tr> <tr><td>9</td><td>720P(1280X720)</td></tr> <tr><td>10</td><td>D1_PAL(720X576)</td></tr> <tr><td>11</td><td>D1_NTSC(720X480)</td></tr> <tr><td>12</td><td>HALF_D1_PAL(720X288)</td></tr> <tr><td>13</td><td>HALF_D1_NTSC(720X240)</td></tr> <tr><td>14</td><td>4CIF_PAL(704X576)</td></tr> <tr><td>15</td><td>4CIF_NTSC(704X480)</td></tr> <tr><td>16</td><td>HALF_4CIF_PAL(704X288)</td></tr> </table>		Video type(2bit)	Resolution (6bit)	8	1080p (1920 x 1080)	9	720P(1280X720)	10	D1_PAL(720X576)	11	D1_NTSC(720X480)	12	HALF_D1_PAL(720X288)	13	HALF_D1_NTSC(720X240)	14	4CIF_PAL(704X576)	15	4CIF_NTSC(704X480)	16	HALF_4CIF_PAL(704X288)	Video Type(1~2) Resolution (8~24)
Video type(2bit)	Resolution (6bit)																						
8	1080p (1920 x 1080)																						
9	720P(1280X720)																						
10	D1_PAL(720X576)																						
11	D1_NTSC(720X480)																						
12	HALF_D1_PAL(720X288)																						
13	HALF_D1_NTSC(720X240)																						
14	4CIF_PAL(704X576)																						
15	4CIF_NTSC(704X480)																						
16	HALF_4CIF_PAL(704X288)																						

	17	HALF_4CIF_NTSC(704X240)	
	18	VGA(640X480)	
	19	CIF_PAL(352X288)	
	20	CIF_NTSC(352X240)	
	21	QVGA(320x240)	
	22	QCIF_PAL(176X144)	
	23	QCIF_NTSC(176X120)	
	24	QQVGA(160X120)	
E	Quality	1~10	
F	Encode mode (0: CBR, 1: VBR)	0/1	
G	Compress mode (0: MJPEG (PNP1), 1: MPEG4 (PNP2) 2: MPEG4 (PNP2), 3: H264 (PNP2), 4: MJPEG (PNP2))	0~4	
H	Frame rate	1~30	
I	Camera Mount type (0 : normal, 1: flip)	0/1	
J	PTZ direction (0: normal, 1: reverse)	0/1	
K	image control (0 : play, 1 : stop)		
L	String Camera Name	16chr	
M	String Camera Mac Address	18chr	

- Notify
 - is not used in this command
- Notify Response
 - is not used in this command

2-2-4. [NVS]

Command Definition: Server sends the notification whenever its status is changed.

- Request
 - is not used in this command
- Response
 - is not used in this command
- Notify
 - is not used in this command

.“STR”	P.S	“NVS”	PARAM	“_END”
--------	-----	-------	-------	--------

➤ Motion Tracking & Detect Status & Video Format & Focus Mode & IRIS Mode & Flip On/Off

➤ Sample Code (Unit : Byte)

‘S’	‘T’	‘R’	‘T’	0	‘0’	‘0’	‘0’	‘C’	‘N’	‘V’	‘S’	0	Param (1Byte)
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	---	-----------------

'_'	'E'	'N'	'D'	0
-----	-----	-----	-----	---

➤ Structure of Parameter (Unit: byte)

1	1	1	2	1	1	1
Focus Mode	IRIS Mode	Flip On/Off	Reserved	Video Format	Motion Tracking	Motion Detect

MSB

LSB

- Focus : 0(AUTO), 1(MANUAL, SEMIAUTO)
- IRIS : 0(AUTO,SHUTTER,BRIGHT), 1(IRIS, MANUAL)
- Notify Response
- is not used in this command

2-2-5. [SDM, RSM]

Command Definition: Motion Detection Setup

■ Request

"STR"	P.S	"SDM"	PARAM	_END"
-------	-----	-------	-------	-------

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'6'	'S'	'D'	'M'	0	Param (2Byte)
'_'	'E'	'N'	'D'	0									

■ Response

"STR"	P.S	"RSM"	P RAM	_END"
-------	-----	-------	-------	-------

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'6'	'R'	'S'	'M'	0	Param (2Byte)
'_'	'E'	'N'	'D'	0									

➤ Structure of Parameter (Unit: byte)

OP CODE	Data	Size Of Data
0x40	0 : Off, 1 : Detect On, 2 : Tracking On	Motion Detect/Tracking On/Off(1)
0x41	0 ~ 255	Detect area map(54) : PENTA
0x42	0 ~ 7	Sensitivity(1)
0x43	1 ~ 63	Pixel difference threshold(1)
0x44	1 ~ 127	Different pixel count threshold(1)
0x45	1 ~ 255	Motion MB count threshold(1)
0x46	1 ~ 255	Motionless frame count threshold(1)
0x47	0 : normal, 1 : skip	Motionless record mode(1)

0x48	0 : none, 1 : Sensor out, 2 : Alert Sound, 3 : Both	Motion detect Action(1)
0x4A	0 ~ 255	Detect area map(72) PNP2

[Detect area map(72) PNP2] – 4(32bit)Byte * 18(Column)

Resolution	Block Count	Mount Type	Width(SD) -Pixel	Height(SD) -Pixel	Width(HD) -Pixel	Height(HD) -Pixel
1080i(1920*1080)	20*16				96	67
720p(1280*720)	16*9				80	80
D1(720*576) 4CIF(704*576)	9*6	PAL	80	96	80	96
D1(720*480) 4CIF(704*480)	9*6	NTSC	80	80	80	80
CIF(352*288)	4*3	PAL	88	96	88	96
CIF(352*240)	4*3	NTSC	88	80	88	80

➤ On/Off status of Motion Detect should be referred the command “NVS”

Parameter	Higher	High	Normal	Low	Lower
Sensitivity	1	2	3	4	5
Pixel Difference threshold	8	12	16	20	24
Different Pixel Count threshold	4	12	20	28	36
Motion MB Count threshold	1	1	2	3	4
Motionless Frame Count threshold	5	5	5	5	5

- Notify
 - is not used in this command
- Notify Response
 - is not used in this command

2-2-6. [RMT]

Command Definition: Video Setup information (Response)

- Request
 - is not used in this command
- Response

“STR”		P.S	“RMT”	PARAM	“_END”											
➤ Sample Code (Unit : Byte)																
‘S’	‘T’	‘R’	‘T’	0	‘0’	‘0’	‘1’	‘E’	‘R’	‘M’	‘T’	0	Param (26Byte)			
‘_’	‘E’	‘N’	‘D’	0												
➤ Structure of Parameter (Unit: byte)																
2	2	22														
a	b	c														
MSB								LSB								
➤ Structure of Parameter (Unit: byte)																
Para	Description															Range
a	Horizon Width															
b	Vertical Height															
c	Reserved															
■ Notify																
➤ is not used in this command																
■ Notify Response																
➤ is not used in this command																

2-2-7. [PTZ], [SCF]

Command Definition: PTZ and IO Control Command

■ Request

“STR”	P.S	“PTZ”	OP CODE	PARAM	“_END”
-------	-----	-------	---------	-------	--------

➤ Structure of Parameter is depending on OP code for PTZ, IO, Function

Operation	Code	Operation	Code	Operation	Code
Pan/Tilt		Focus		PTZ Position	
*Tilt Up	20	Focus Far	26	*Set Pan Position	125
*Tilt Down	21	Focus Near	27	*Set Tilt Position	126
*Pan Left	22	Focus Stop	47	*Set Zoom Position	127
*Pan Right	23	Iris		*Set PTZ Position	37
*Pan Right, Tilt Up	33	Iris Open	28	Get Pan Position	100
*Pan Right, Tilt Down	34	Iris Close	29	Get Tilt Position	101
*Pan Left, Tilt Down	35	Function		Get Zoom Position	128

*Pan Left, Tilt Up	36	*Preset Save	74	Get PTZ Position	130
Pan/Tilt Stop	41	*Preset Delete	104	Alarm I/O	
*Set Pan/Tilt Speed	105	*Preset Run	75	*Set Output	106
Zoom		*Pattern Run	71	Get Input Status	102
Zoom In (Tele)	24	*Scan Run	79	Get Output Status	103
Zoom Out (Wide)	25	*Group Run	80	OSD Menu	
Zoom Stop	45			OSD Menu On/Off	108
Additional Function for HD-1					
*Pattern Save	70	*Pattern Delete	72	Load All Pattern	73
*Scan Save	67	*Scan Delete	68	Load All Scan	69
*Group Save	82	*Group Delete	83	Load All Group	84
				Load All Preset	76
*Set Zoom Advanced	120	Get Zoom Advanced	121		
*Set PTZ Advanced	122	Get PTZ Advanced	123		


“*” marked Operations in the table needs to refer the following Parameter definition

- Parameter Format: LSB(1Byte) + MSB(1Byte)
- Number of Alarm In/Out and Preset, Pattern, Scan, Group is depending on Edge device model.

	HD-1	SD-1	SD-2
MAX_PRESET	1024	255	255
MAX_PATTERN	128	4	4
MAX_SCAN	128	8	8
MAX_GROUP	128	8	8
ALARM INPUT	2	2	8
ALARM OUTPUT	1	1	4

- in the case of PROBE model of HD-1, it can request the current setting(=saved) of Preset, Pattern, Scan and Group using the Load Function(Op code 76, 73, 69, 84) and respective request can be responded from each Save Command.
- Advanced Zoom Command (OP code 120, 121, 122, 123) works from firmware version v0.9.23_20110530(PTI-H2100), v0.9.67_20110530(PMI-H2000, PMI-H2000s).
- Structure of Parameter is depending on OP code

Operation	OP Code	Parameters (bytes)
-----------	---------	--------------------

	Tilt Up	20	
	Tilt Down	21	
	Pan Left	22	
	Pan Right	23	
	Pan Right, Tilt Up	33	SPEED(2) <i>SPEED</i> 1 ~ 1000
	Pan Right, Tilt Down	34	
	Pan Left, Tilt Down	35	
	Pan Left, Tilt Up	36	
	Set Pan/Tilt Speed	105	
	Preset Save	74	
	Preset Run	75	
	Preset Delete	104	INDEX(2) <i>INDEX</i> 1 ~ MAX_PRESET
	Pattern Save	70	(HD-1 Only) Example of pattern drawing:  ※ in the case of pattern drawing like above example, it has 6 SUB_POINTS and its starting point will be SUB_POINT_1. ※ The number of created SUB_POINT cannot exceed more than 55. INDEX(2)+SUB_POINT_NUM(1)+SUB_POINT_1_PAN(2)+ SUB_POINT_1_TILT(2)+SUB_POINT_1_ZOOM(2)+ SUB_POINT_1_SPEED(2)+SUB_POINT_1_DIR(1)+SUB_ POINT_2_PAN(2)+...+SUB_POINT_n_PAN(2)+SUB_POI NT_n_TILT(2)+SUB_POINT_n_ZOOM(2)+SUB_POINT_n_ SPEED(2)+SUB_POINT_n_DIR(1)+LABEL(10)

		<p>INDEX <i>//pattern number, 1 ~ MAX_PATTERN</i></p> <p>SUB_POINT_NUM <i>//total number of created SUB_POINT_n in one pattern (n)</i></p> <p>SUB_POINT_n_PAN <i>//PAN location of SUB_POINT_n, 0 ~ 36000</i></p> <p>SUB_POINT_n_TILT <i>//TILT location of SUB_POINT_n 0 ~ 9000</i></p> <p>SUB_POINT_n_ZOOM <i>//Zoom ratio of SUB_POINT_n, 1 ~ MAX_ZOOM</i></p> <p>SUB_POINT_n_SPEED <i>//Moving speed to SUB_POINT_n</i> 3 : Very Slow 7 : Slow 11 : Middle 15 : Fast 300 : Skip</p> <p>SUB_POINT_n_DIR <i>//moving direction of SUB_POINT_n</i> 0 : shortest path, 1 : clock-wise, 2 : anti-clockwise</p> <p>LABEL <i>//name of Pattern created</i></p>
Pattern Run	71	INDEX(2)
Pattern Delete	72	<p>INDEX <i>1 ~ MAX_PATTERN</i></p>
Scan Save	67	<p>(HD-1 Only)</p> <p>INDEX(2)+1ST_POS(2)+2ND_POS_NUM(2)+SPEED(2)+ LABEL(10)</p> <p>INDEX <i>//1 ~ MAX_SCAN</i></p> <p>1ST_POS <i>//1st Preset Number, 1 ~ MAX_PRESET</i></p> <p>2ND_POS <i>//2nd Preset Number, 1 ~ MAX_PRESET</i></p> <p>SPEED <i>// moving speed between 1st – 2nd Presets, 1 ~ 360</i></p> <p>SCAN_LABEL <i>//Scan Name</i></p>
Scan Run	79	INDEX(2)
Scan Delete	68	<p>INDEX <i>1 ~ MAX_SCAN</i></p>
Group Save	82	<p>(HD-1 Only)</p> <p>One Group can be consisted with maximum 10 Sub Index.</p> <p>INDEX(2)+SUB_1_ACTION(1)+SUB_1_ACTION_IDX(2)+ SUB_1_DWELL(2)+SUB_1_OPT(2)+SUB_2_ACTION(1)+ ...+SUB_20_OPT(2)+LABEL(10)</p> <p>INDEX <i>//Group number, 1 ~ MAX_GROUP</i></p>

		<p>SUB_n_ACTION (n = 1 ~ 20) // Sub Index Action (Nth) //0 : None, 1 : Preset, 2 : Pattern, 3 : Scan</p> <p>SUB_n_ACTION_IDX (n = 1 ~ 20) //Function Index of Sub Index(Nth),1 ~ MAX_FUNCTION</p> <p>SUB_n_DWELL (n = 1 ~ 20) //Waiting time for Sub Index(Nth),3 sec ~ 240 sec</p> <p>SUB_n_OPT (n = 1 ~ 20) //Sub Index Option(Nth), Moving speed or repeat count //if required Action is Preset, then this parameter stands for moving speed //if required Action is Pattern or Scan, then it stands for repeat count. 1 ~ 360</p> <p>LABEL //Group Name</p>
Group Run	80	INDEX(2) <i>INDEX</i> <i>1 ~ MAX_GROUP</i>
Set Pan Position	125	PAN_POS(2) <i>PAN_POS</i> <i>0 ~ 36000</i>
Set Tilt Position	126	TILT_POS(2) <i>TILT_POS</i> <i>0 ~ 9000, when model is PMI-H2000</i> <i>0 ~ 18000</i>
Set Zoom Position	127	ZOOM_POS(2) <i>ZOOM_POS</i> <i>1 ~ MAX_ZOOM</i>
Set PTZ Position	37	PAN_POS(2)+TILT_POS(2)+ZOOM_POS(2) <i>PAN_POS</i> <i>0 ~ 36000</i> <i>TILT_POS</i> <i>0 ~ 18000</i> <i>0 ~ 9000, when model is PMI-H2000</i> <i>ZOOM_POS</i> <i>1 ~ MAX_ZOOM</i>
Set Output	106	INDEX(1)+ STATUS(1) <i>INDEX (BitMask)</i> <i>1 : Output-1, 2 : Output-2, 4 : Output-3, 8 : Output-4</i> <i>STATUS</i> <i>0 : off, 1 : On</i>
OSD Menu	108	(SD-1, SD-2 Only) MENU_MODE(1) <i>MENU_MODE</i> <i>0 : off, 1 : On</i> <i>(Reference)</i> <i>*Arrow moving in MENU → LEFT/RIGHT/UP/DOWN + STOP</i> <i>*MENU ENTER → FOCUS_NEAR + FOCUS_STOP</i> <i>MENU CANCEL → FOCUS_FAR + FOCUS_STOP</i>
Set Zoom Advanced	120	(HD-1 Only) ZOOM_POS(2) <i>ZOOM_POS</i> <i>100 ~ MAX_ZOOM*100</i>
Set PTZ Advanced	122	(HD-1 Only)

		PAN_POS(2)+TILT_POS(2)+ZOOM_POS(2) PAN_POS 0 ~ 36000 TILT_POS 0 ~ 18000 0 ~ 9000, when model is PMI-H2000 ZOOM_POS 100 ~ MAX_ZOOM*100
--	--	--

➤ OP code for Zoom Camera Control (**HD-1 Only**)

Operation	Code	Operation	Code	Operation	Code
White Balance		Auto Exposure		Etc.	
*Set WB Mode	1 1	*Set AE Mode	157	*Set Day & Night Mode	170
*Set R-Gain	153	*Set Shutter	160	*Set Focus Mode	172
*Set B-Gain	154	*Set Iris	161	*Set Backlight	155
Set One Push Trigger	152	*Set Gain	162	*Set Digital Zoom	150
Get WB Mode	181	*Set Bright	163	Get Day & Night Mode	200
Get R-Gain	183	Get AE Mode	187	Get Focus Mode	202
Get B-Gain	184	Get Shutter	190	Get Backlight	185
		Get Iris	191	Get Digital Zoom	180
		Get Gain	192		
		Get Bright	193		

➤ Structure of Parameter is depending on OP code (**HD-1 Only**)

Operation	OP Code	Parameters (bytes)
WB Mode	151	MODE(1) MODE 1:Auto, 2:Indoor, 3:Outdoor, 4:One-Push, 5:Manual
R-Gain	153	MODE(1)+VALUE(1) MODE 2:Up, 3:Down, 4:Direct VALUE 0 ~ 255, when Mode is Direct.
B-Gain	154	MODE(1)+VALUE(1) MODE 2:Up, 3:Down, 4:Direct VALUE 0 ~ 255, when Mode is Direct.
AE Mode	157	MODE(1) MODE 1:Full Auto, 2:Manual, 3:Shutter Priority, 4:Iris Priority, 5:Bright, 6:Spotlight
Shutter	160	MODE(1)+VALUE(1) MODE 2:Up, 3:Down, 4:Direct

		VALUE 1 ~ 21, when Mode is Direct.
Iris	161	MODE(1)+VALUE(1) MODE 2:Up, 3:Down, 4:Direct VALUE 0 ~ 17, when Mode is Direct.
Gain	162	MODE(1)+VALUE(1) MODE 2:Up, 3:Down, 4:Direct VALUE 0 ~ 7, when Mode is Direct.
Bright	163	MODE(1)+VALUE(1) MODE 2:Up, 3:Down, 4:Direct VALUE 0 ~ 23, when Mode is Direct.
Day & Night Mode	170	MODE(1) MODE 1:Day, 2:Night, 3:Auto
Focus Mode	172	MODE(1) MODE 1:Auto, 2:Manual, 3:Semi-Auto
Backlight	155	MODE(1) MODE 1:On, 2:Off
Digital Zoom	150	MODE(1) MODE 1:On, 2:Off

■ Response

“STR”	P.S	“SCF”	OP CODE	PARAM	“_END”
-------	-----	-------	---------	-------	--------

➤ Structure of Parameter

Operation	OP Code	Parameters (bytes)
Preset Save	74	(HD-1 Only) INDEX(2)+PAN(2)+TILT(2)+ZOOM(2)+LABEL(10) INDEX 1 ~ MAX_PRESET PAN 0 ~ 360000 TILT 0 ~ 180000 ZOOM 1 ~ MAX_ZOOM LABEL Preset Name, String
Preset Delete	104	(HD-1 Only) INDEX(2) INDEX 1 ~ MAX_PRESET

		(HD-1 Only) This is operation for HD-1 type of camera to the respond to the Pattern Save and Load All Pattern.
Pattern Save	70	<pre> INDEX(2)+SUB_POINT_NUM(1)+SUB_POINT_1_PAN(2)+ SUB_POINT_1_TILT(2)+SUB_POINT_1_ZOOM(2)+ SUB_POINT_1_SPEED(2)+SUB_POINT_1_DIR(1)+SUB_ POINT_2_PAN(2)+...+SUB_POINT_n_PAN(2)+SUB_POI NT_n_TILT(2)+SUB_POINT_n_ZOOM(2)+SUB_POINT_n SPEED(2)+SUB_POINT_n_DIR(1)+LABEL(10) </pre> <pre> INDEX //Pattern Number, 1 ~ MAX_PATTERN SUB_POINT_NUM //total number of created SUB_POINT_n in one pattern (n) SUB_POINT_n_PAN //PAN location of SUB_POINT_n, 0 ~ 36000 SUB_POINT_n_TILT //TILT location of SUB_POINT_n 0 ~ 9000 SUB_POINT_n_ZOOMz //Zoom ratio of SUB_POINT_n, 1 ~ MAX ZOOM SUB_POINT_n_SPEED //Moving speed to SUB_POINT_n 3 : Very Slow 7 : Slow 11 : Middle 15 : Fast 300 : Skip SUB_POINT_n_DIR //Moving direction to SUB_POINT_n 0 : shortest 1 : clock-wise, 2 : anti-clockwise LABEL //Pattern Name </pre>
Patter Delete	72	(HD-1 Only) INDEX(2) <i>INDEX</i> //1 ~ MAX_PATTERN
Scan Save	67	(HD-1 Only) Responding to Scan Save / Load All Scan INDEX(2)+1 ST _POS(2)+2 ND _POS_NUM(2)+SPEED(2)+ LABEL(10) <i>INDEX</i> //1 ~ MAX_SCAN 1 ST _POS //1st Preset Number , 1 ~ MAX_PRESET 2 ND _POS //2nd Preset Number, 1 ~ MAX_PRESET

		<p>SPEED <i>//Moving speed between 1st – 2nd Preset 1 ~ 360</i></p> <p>SCAN_LABEL <i>Scan Name</i></p>
Scan Delete	68	<p>(HD-1 Only)</p> <p>INDEX(2) <i>INDEX 1 ~ MAX_SCAN</i></p>
		<p>(HD-1 Only)</p> <p>Responding to the Group Save / Load All Group</p>
		<p>INDEX(2)+SUB_1_ACTIOIN(1)+SUB_1_ACTION_IDX(2)+ SUB_1_DWELL(2)+SUB_1_OPT(2)+SUB_2_ACTION(1)+ ...+SUB_20_OPT(2)+LABEL(10)</p>
Group Save	82	<p>INDEX <i>//Group Number, 1 ~ MAX_GROUP</i></p> <p>SUB_n_ACTION (n = 1 ~ 20) <i>//Action of SUB_INDEX_n</i> <i>0 : None, 1 : Preset, 2 : Pattern, 3 : Scan</i></p> <p>SUB_n_ACTION_IDX (n = 1 ~ 20) <i>//Function Index of SUB_INDEX_n, 1 ~ MAX_FUNCTION</i></p> <p>SUB_n_DWELL (n = 1 ~ 20) <i>//Holding time for SUB_INDEX_n, 3 sec ~ 240 sec</i></p> <p>SUB_n_OPT (n = 1 ~ 20) <i>//Option(moving speed or repeat count) of SUB_INDEX_n //if required Action is Preset, then this parameter stands for moving speed //if required Action is Pattern or Scan, then it stands for repeat count. 1 ~ 360</i></p> <p>LABEL <i>//Group Name</i></p>
Group Delete	83	<p>(HD-1 Only)</p> <p>INDEX(2) <i>// INDEX, 1 ~ MAX_GROUP</i></p>
Get Pan Position	100	<p>PAN_POS(2) <i>PAN_POS 0 ~ 36000</i></p>
Get Tilt Position	10	<p>TILT_POS(2) <i>TILT_POS 0 ~ 18000</i></p>
Get Zoom Position	128	<p>ZOOM_POS(2) <i>ZOOM_POS 1 ~ MAX_ZOOM</i></p>
Get PTZ Position	130	<p>PAN_POS(2)+TILT_POS(2)+ZOOM_POS(2) <i>PAN_POS 0 ~ 36000</i></p> <p>TILT_POS <i>0 ~ 18000</i></p> <p>ZOOM_POS</p>

		1 ~ MAX_ZOOM
Get Input Status	102	<p>INPUT_NUM(2) INPUT_NUM 1 : Input-1, 2 : Input-2, 4 : Input-3, 8 : Input-4</p> <p>(Reference)</p> <p>1. When Alarm Input generated, the command of "Get Input Status" will be delivered periodically. Once the alarm input will be off(event off), then no more command will be delivered</p> <p>2. If both off "Input one" and "Input two" are generated at the same time, each and respective command will be delivered</p>
Get Output Status	103	<p>OUTPUT_NUM(2) OUTPUT_NUM (BitMask) 1 : Output-1, 2 : Output-2, 4 : Output-3, 8 : Output-4</p>
Get Zoom Advanced	121	<p>ZOOM_POS(2) ZOOM_POS 100 ~ MAX_ZOOM*100</p>
Get PTZ Advanced	123	<p>PAN_POS(2)+TILT_POS(2)+ZOOM_POS(2) PAN_POS 0 ~ 36000 TILT_POS 0 ~ 18000 ZOOM_POS 100 ~ MAX_ZOOM*100</p>

➤ Structure of Parameter is depending on OP code. (**HD-1 Only**)

Operation	OP Code	Parameters (bytes)
WB Mode	181	MODE(1) 1:Auto, 2:Indoor, 3:Outdoor, 4:One-Push, 5:Manual
R-Gain	183	GAIN(1) 0 ~ 255
B-Gain	184	GAIN(1) 0 ~ 255
AE Mode	187	MODE(1) 1:Full Auto, 2:Manual, 3:Shutter Priority, 4:Iris Priority, 5:Bright, 6:Spotlight
Shutter	190	VALUE(1) 1 ~ 21
Iris	191	VALUE(1) 0 ~ 17
Gain	192	VALUE(1) 0 ~ 7
Bright	193	VALUE(1) 0 ~ 23
Day & Night Mode	200	MODE(1) 1:Day, 2:Night, 3:Auto
Focus Mode	202	MODE(1) 1:Auto, 2:Manual, 3:Semi-Auto

Backlight	185	MODE(1) 1:On, 2:Off
Digital Zoom	180	MODE(1) 1:On, 2:Off

■ Notify
 ➤ is not used in this command
 ■ Notify Response
 ➤ is not used in this command

2-2-8. [FSR]

Command Definition: Encoder Setup

■ Request

“STRT”	P.S	“FSR”	PARAM	“_END”
--------	-----	-------	-------	--------

➤ Sample Code (Unit : Byte)

‘S’	‘T’	‘R’	‘T’	0	‘0’	‘0’	‘0’	‘1’	‘F’	‘S’	‘R’	0	Param (1Byte)
‘_’	‘E’	‘N’	‘D’	0									

➤ Param : Channel Number (0 ~ 4)


■ Response

“STRT”	P.S	“FSR”	PARAM	“_END”
--------	-----	-------	-------	--------

➤ Sample Code (Unit : Byte)

‘S’	‘T’	‘R’	‘T’	0	‘0’	‘0’	‘8’	‘9’	‘F’	‘S’	‘R’	0	Param (137Byte)
‘_’	‘E’	‘N’	‘D’	0									

➤ Structure of Parameter (Unit: byte)



Para	Description	Range
a	Setup Channel Number	0~4
b	Codec Type(0:None, 1:H264, 2:MPEG4, 3:JPEG) ch1/ch2 : Fixed ch3/ch4/ch5 : Variable	0~3
c	Frame rate(NTSC:1~30, PAL:1~25)	1~25 1~30

d	Max Frame rate(NTSC:30, PAL:25)	30/25
e	Bit Rate Mode(0:VBR, 1:CBR)	0/1
f	Bit Rate(1~5Mbps)	1~5
g	Quality(1:best ~ 5:worst)	1~5
h	Resolution(0:1080i, 1:720p, 2:D1,4CIF, 3:CIF, 4:QCIF)	0~4
i	Gop Interval(1~30, default:15)	1~30
j	Priority(Not yet)	0~10
k	Quantizer(Not yet)	0~10
l	Video Name	32chr
m	Codec Name	32chr
n	Reserved	32chr

- Notify
 - is not used in this command
- Notify Response
 - is not used in this command

2-2-9. [FSP]

Command Definition: Encoder Setup

■ Request

“STRT”	P.S	“FSP”	PARAM	“_END”
➢ Sample Code (Unit : Byte)				
‘S’	‘T’	‘R’	‘T’	0 ‘0’ ‘0’ ‘8’ ‘9’ ‘F’ ‘S’ ‘P’ 0 Param (137Byte)
‘_’	‘E’	‘N’	‘D’	0

➢ Structure of Parameter (Unit: byte)

1	4	4	4	4	4	4	4	4	4	4	32	32	32
a	b	c	d	e	F	g	h	i	j	k	l	m	n

MSB LSB

Para	Description	Range
a	Setup Channel Number	0~4
b	Codec Type(0:None, 1:H264, 2:MPEG4, 3:JPEG) ch1/ch2 : Fixed ch3/ch4/ch5 : Variable	0~3
c	Frame rate(NTSC:1~30, PAL:1~25)	1~25

		1~30
d	Max Frame rate(NTSC:30, PAL:25)	30/25
e	Bit Rate Mode(0:VBR, 1:CBR)	0/1
f	Bit Rate(1~5Mbps)	1~5
g	Quality(1:best ~ 5:worst)	1~5
h	Resolution (0:1080i, 1:720p, 2:D1,4CIF, 3:CIF, 4:QCIF)	0~4
i	Gop Interval(1~30, default:15)	1~30
j	Priority(Not yet)	0~10
k	Quantizer(Not yet)	0~10
l	Video Name	32chr
m	Codec Name	32chr
n	Reserved	32chr

■ Response

“STR”	P.S	“FSP”	PARAM	“_END”
-------	-----	-------	-------	--------

➤ Sample Code (Unit : Byte)

➤ Param : Success(“OK”), Fail(“FAIL”)

‘S’	‘T’	‘R’	‘T’	0	‘0’	‘0’	‘0’	‘4’	‘F’	‘S’	‘P’	0	Param (5Byte)
‘_’	‘E’	‘N’	‘D’	0									

■ Notify

➤ is not used in this command

■ Notify Response

➤ is not used in this command

2-2-10. [AGN]

Command Definition : Get Alarm I/O Number Command

■ Request

“STR”	P.S	“AGN”	PARAM	“_END”
-------	-----	-------	-------	--------

➤ Sample Code (Unit : Byte)

‘S’	‘T’	‘R’	‘T’	0	‘0’	‘0’	‘8’	‘D’	‘A’	‘G’	‘N’	0	Param (0Byte)
‘_’	‘E’	‘N’	‘D’	0									

■ Response

“STR”	P.S	“AGN”	PARAM	“_END”
-------	-----	-------	-------	--------

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'9'	'A'	'G'	'N'	0	Param (2Byte)
'_'	'E'	'N'	'D'	0									

➤ Structure of Parameter (Unit: byte)

1	1
a	b

MSB LSB

Para	Description	Range
a	Alarm In Number	0~255
b	Alarm Out Number	0~255


■ Notify

➤ is not used in this command

■ Notify Response

➤ is not used in this command

2-3. Firmware Upload & Update



2-3-1 [FUP, FUR]

Command Definition: Upload Request Command

■ Request

"STRT"	P.S	"FUP"	PARAM	"_END"
--------	-----	-------	-------	--------

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'5'	'7'	'C'	'F'	'U'	'P'	0	Param (1400Byte)
'_'	'E'	'N'	'D'	0									

➤ Structure of Parameter (Unit: byte)

4	4	4	2	2	4	size	
a	b	c	d	e	f	g	

Para	Description	Range
a	File Type (Not yet).	
b	Total size	
c	CRC for the file to be upgraded	
d	Slice Number (starting from "0")	
e	Slice Size	
f	Slice CRC	
G	Slice Data At least same with "1400 – (A+B+C+D+E+F)" or less.	

■ Response

"STRT"	P.S	"FUR"	PARAM	"_END"
--------	-----	-------	-------	--------

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'C'	'F'	'U'	'R'	0	Param (13Byte)
'_'	'E'	'N'	'D'	0									

➤ Structure of Parameter (Unit: byte)

variable	1	4
a	b	c

LSB MSB

Para	Description	Range
a	Success - "OK" (2byte) Fail - "FAIL" (4byte) Complete - "COMPLETE" (8byte)	
b	\n	
c	Receive File Size	

■ Notify

➤ is not used in this command

■ Notify Response

➤ is not used in this command

2-3-2 [FUS]

Command Definition: Upload Status Command

- Request
 - is not used in this command


- Response
 - is not used in this command
- Notify

"STR"	P.S	"FUS"	PARAM	"_END"
--------------	------------	--------------	--------------	---------------

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'C'	'F'	'U'	'S'	0	Param (8Byte)
'_'	'E'	'N'	'D'	0									

➤ Structure of Parameter (Unit: byte)



Para	Description	Range
A	Result Code // Boot Status 110 ~ 190 110: complete. Upgrade Complete 120: error. Upgrade Error 130: ready. Upgrade Ready 140: progress. Upgrade in Progress 150: start. Verify & Loading. // Kernel Status 210 ~ 290 210: complete. 220: error. 230: ready. 240: progress. 250: start. // Root1 Status 310 ~ 390	

	<p>310: complete.</p> <p>320: error.</p> <p>330: ready.</p> <p>340: progress.</p> <p>350: start.</p> <p><i>// Root2 Status 410 ~ 490</i></p> <p>410: complete.</p> <p>420: error.</p> <p>430: ready.</p> <p>440: progress.</p> <p>450: start.</p> <p><i>// Config Status 510 ~ 590</i></p> <p>510: complete.</p> <p>520: error.</p> <p>530: ready.</p> <p>540: progress.</p> <p>550: start.</p> <p><i>// Status 610 ~ 690</i></p> <p>640: File Break.</p> <p>650: System Rebooting.</p> <p><i>// Internal Analog(Micom) Status 710 ~790</i></p> <p>710: complete.</p> <p>720: error.(Upgrade Fail)</p> <p>730: ready.</p> <p>740: progress.</p> <p>750: start.</p> <p>760: Different File (detecting the incorrect file in updating)</p> <p>770: Old(=previous) file is not exited after Upgrade fail.</p> <p>780: Old(=Previous) file is fall-backed successfully after Upgrade fail.</p> <p>790: Fall-back failure after upgrade fail</p>	
B	<p>Result Param</p> <p>Code [progress] -> percentage of progress</p>	

- Notify Response
 - is not used in this command

2-4. Usage Reference

2-4-1. Relay setting setup

- Server
 - Alarm or Motion Detection → Alarm Out initialized (Motion is handled by 'Action')
 - Relay becomes "ON" automatically
- Client
 - Relay Event generated by Client manually to turn on/off of "Relay".
 - Relay On (OP_CODE:106, Param1:1, Param2:1) – Relay (#1) becomes "ON"
 - Relay Off (OP_CODE:106, Param1:1, Param2:0) – Relay (#1) becomes "OFF"
 - Relay On / Off


OP_CODE	PARAM 1	PARAM 2
106	Relay No (Bit Mask) Out1 : 1 Out2 : 2 Out3 : 4 Out4 : 8	On/Off On : 1 Off : 0

2-4-2. Alarm Input Setting

- Alarm Input (1 / 2)
 - Select the setting which alarm(sensor) input is
- Input Device Setup (Off / N.O / N.C)
 - Setup the type of alarm input.
 - Available to setup for alarm sensor type ("don't use sensor event" / "normal open type"/ "normal close type")
- Activation Time (Always / Only Scheduled Time)
 - Set up the Activation Time (Check it always / Check it only scheduled day/time)
- Action (Alarm Output / Output Duration / Alarm Image Transfer / Camera Action)
 - Generating alarm output (when alarm happened) as following the configured duration for alarm output
 - If "Alarm Image Transfer" is "ON", then stored image from alarm will be sent via configured Transfer mode (FTP or Email).however Image cannot be sent without setting of Admin in FTP' and SMTP even though 'Alarm Image Transfer' set 'On'
 - Available to set up the motion of Camera when alarm generate.

3. Video Server Protocol

This is protocol for Video Server.



- ✓ Video Port(Channel) can be connected only if it is 'LGS'
- ✓ Random Value in "CNS" response take 1 second to be created inside Camera

3-1. Connection Command

3-1-1. [CNS]

Command Definition: Response to Connection Request from client

- Request (Client -> Server) to connect to the server
- Response (Server -> Client) for the Connection Request

"STR"	P.S	CTR	"CNS"	NULL	"_END"
--------------	------------	------------	--------------	-------------	---------------

➤ "CNS" message is required before Authorization.

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'0'	'C'	'N'	'S'	0
'_'	'E'	'N'	'D'	0									

- Notify (Server -> Client)

➤ is not used in this command

- Notify Response (Client -> Server)

➤ is not used in this command

3-1-2. [LGN]

Command Definition: User Authentication (Request)

- Request

"STR"	P.S	"LGN"	RANDOM CONST	USER ID + PW	"_END"
--------------	------------	--------------	---------------------	---------------------	---------------

➤ ID: 20byte,

➤ PW: 20byte

➤ RANDOM CONST : use RANDOM CONST parameter received from control connection

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'2'	'C'	'L'	'G'	'N'	0	RANDOM CONST (4Byte)
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	---	------------------------

ID (20byte)	Password (20byte)
'_ 'E' 'N' 'D' 0	

■ Response
 ➤ is not used in this command
 ■ Notify
 ➤ is not used in this command.
 ■ Notify Response
 ➤ is not used in this command

3-1-3. [LGS], [LGW]

Command Definition: User Authentication Message(Response)

- Request
 ➤ is not used in this command
- Response

"STR"	P.S	CTR	"LGS"	NULL	"_END"
➤ Authorization Success Message					
➤ Sample Code (Unit : Byte)					

➤ User Authorization Failure Message.

➤ Sample Code (Unit : Byte)

"S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'0'	'L'	'G'	'S'	0	'_ '	'E'	'N'	'D'	0
"STR"																		
"LGW"																		

"S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'0'	'L'	'G'	'W'	0	'_ '	'E'	'N'	'D'	0
"STR"																		
"LGW"																		

3-1-4. [STA]

Command Definition: Connection status (check) message.

- Request
 ➤ is not used in this command
- Response
 ➤ is not used in this command
- Notify
 ➤ is not used in this command

"STR"	P.S	CTR	"STA"	NULL	"_END"
-------	-----	-----	-------	------	--------

- Check message for the connection status (every 10 seconds)

- Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'0'	'S'	'T'	'A'	0	'_'	'E'	'N'	'D'	0
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	-----	---	-----	-----	-----	-----	---

■ Notify Response

"STRT"	P.S	"STA"	NULL	_END
--------	-----	-------	------	------

- Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'S'	'T'	'A'	0	'_'	'E'	'N'	'D'	0
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	---	-----	-----	-----	-----	---

3-2. Transmitting Stream Data

Motion Detection Info (72Byte)	STREAM DATA
----------------------------------	-------------


- Both of "I-Frame" and "P- Frame" are set with 72Byte.
- Default value for "I-Frame" is "0".
- Initial "I-Frame" includes the VOL Header after 72Byte set. .
- Structure of Stream Data

Type	Name	Description																																																
unsigned char	start_code[5]	Start Code ("STRT")																																																
unsigned char	packetsize[4]	Packet size																																																
unsigned char	isStream	Packet Type ('1')																																																
unsigned char	isCompMode	Compression Mode																																																
unsigned long	frame_num	frame number																																																
unsigned long	frame_size	frame size																																																
unsigned short	slice_num	Slice Number of Current Packet																																																
unsigned short	slice_size	Slice Size of Current Packet																																																
unsigned char	channel_info	Channel Index																																																
unsigned char	mountType, resolution	<table border="1"> <tr> <td>1</td><td>1</td><td>1</td><td>1</td><td>1</td><td>1</td><td>1</td><td>1</td> </tr> <tr> <td>MountType</td><td>Resolution</td><td colspan="6"></td></tr> <tr> <td>(MSB)</td><td>(LSB)</td><td colspan="6"></td></tr> <tr> <td colspan="8">bit7~6</td></tr> <tr> <td colspan="8"> <table border="1"> <tr> <th>Description</th><th>Value</th></tr> <tr> <td>NONE</td><td>00</td></tr> <tr> <td>NTSC</td><td>01</td></tr> <tr> <td>PAL</td><td>10</td></tr> </table> </td></tr> </table>	1	1	1	1	1	1	1	1	MountType	Resolution							(MSB)	(LSB)							bit7~6								<table border="1"> <tr> <th>Description</th><th>Value</th></tr> <tr> <td>NONE</td><td>00</td></tr> <tr> <td>NTSC</td><td>01</td></tr> <tr> <td>PAL</td><td>10</td></tr> </table>								Description	Value	NONE	00	NTSC	01	PAL	10
1	1	1	1	1	1	1	1																																											
MountType	Resolution																																																	
(MSB)	(LSB)																																																	
bit7~6																																																		
<table border="1"> <tr> <th>Description</th><th>Value</th></tr> <tr> <td>NONE</td><td>00</td></tr> <tr> <td>NTSC</td><td>01</td></tr> <tr> <td>PAL</td><td>10</td></tr> </table>								Description	Value	NONE	00	NTSC	01	PAL	10																																			
Description	Value																																																	
NONE	00																																																	
NTSC	01																																																	
PAL	10																																																	

		bit5 ~ 0
		Description Value
		1920*1080 01000
		1280*720 01001
		720*576 01010
		720*480 01011
		720*288 01100
		720*240 01101
		704*576 01110
		704*480 01111
		704*288 10000
		704*240 10001
		640*480 10010
		352*288 10011
		352*240 10100
		320*240 10101
		176*144 10110
		176*128 10111
		160*120 11000
unsigned long	date_time	Date time (UTC time)
unsigned short	frame_gop_num	gop number
unsigned short	frame_type	
unsigned char	frame_data[1400]	Payload (Stream Data)
unsigned char	end_code[5]	Ending Code ("END")

4. Audio Receive Server Protocol (Audio from Microphone in Client)

The protocol for Audio Receive Server.



- ✓ Audio Port(Channel) can be connected only if it is 'LGS'
- ✓ Random Value in "CNS" response take 1 second to be created inside Camera

4-1. Connection Command

4-1-1. [CNS]

Command Definition: Response to Connection Request from client

- Request (Client -> Server) to connect to the server
- Response (Server -> Client) for the Connection Request

"STR"	P.S	CTR	"CNS"	NULL	"_END"
-------	-----	-----	-------	------	--------

➤ "CNS" message is required before Authorization.

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'0'	'C'	'N'	'S'	0
' '	'E'	'N'	'D'	0									

- Notify (Server -> Client)

➤ is not used in this command

- Notify Response (Client -> Server)

➤ is not used in this command

4-1-2. [LGN]

Command Definition: User Authentication (Request)

- Request

"STR"	P.S	"LGN"	RANDOM CONST	USER ID + PW	"_END"
-------	-----	-------	--------------	--------------	--------

➤ ID: 20byte,

➤ PW: 20byte

➤ RANDOM CONST : use RANDOM CONST parameter received from control connection

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'2'	'C'	'L'	'G'	'N'	0	RANDOM CONST (4Byte)
ID (20byte)							Password (20byte)						
'_'	'E'	'N'	'D'	0									

■ Response

➤ is not used in this command

■ Notify

➤ is not used in this command

■ Notify Response

➤ is not used in this command

4-1-3. [LGS], [LGW]

Command Definition: User Authentication Message(Response)

■ Request

➤ is not used in this command

■ Response

"STR"	P.S	CTR	"LGS"	NULL	"_END"
-------	-----	-----	-------	------	--------

➤ Authentication Success Message

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'		0	'0'	'0'	'0'	'4'	'0'	'L'	'G'	'S'	0	'_'	'E'	'N'	'D'	0
"STR"	P.S	CTR	"LGW"													NULL	"_END"		

➤ Authentication Failure Message

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'0'	'L'	'G'	'W'	0	'_'	'E'	'N'	'D'	0
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	-----	---	-----	-----	-----	-----	---

■ Notify

➤ is not used in this command

■ Notify Response

➤ is not used in this command

4-1-4. [STA]

Command Definition: Connection status (check) message.

■ Request

➤ is not used in this command

■ Response

➤ is not used in this command

■ Notify

"STRT"	P.S	CTR	"STA"	NULL	"_END"
---------------	------------	------------	--------------	-------------	---------------

➤ Check message for the connection status (every 10 seconds)

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'0'	'S'	'T'	'A'	0	'_'	'E'	'N'	'D'	0
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	-----	---	-----	-----	-----	-----	---

■ Notify Response

"STRT"	P.S	"STA"	NULL	"_END"
---------------	------------	--------------	-------------	---------------

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'S'	'T'	'A'	0	'_'	'E'	'N'	'D'	0
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	---	-----	-----	-----	-----	---

4-2. Receiving Stream Data

STREAM DATA


➤ Structure of Stream Data

Type	Name	Description
unsigned char	start_code[5]	Start Code ("STRT")
unsigned char	packetsize[4]	Packet size
unsigned char	isStream	Packet Type ('1')
unsigned char	isCompMode	0x31 = g.711(8bit, mono, 16000 samplerate) 0x11 = g.711(8bit, mono, 8000 samplerate)
unsigned long	frame_num	frame number
unsigned long	frame_size	frame size
unsigned short	slice_num	Slice Number of Current Packet
unsigned short	slice_size	Slice Size of Current Packet
*unsigned char	channel_info	unuse
*unsigned char	resolution	unuse
unsigned long	date_time	Date time (UTC time)
*unsigned short	frame_gop_num	unuse
*unsigned short	frame_type	unuse
unsigned char	frame_data[1400]	Payload (Stream Data)
unsigned char	end_code[5]	Ending Code ("_END")

➤ Signed items are not used in Audio Receiver Server

5. Audio Transmit Server Protocol (Audio from MIC in PNP2/Camera)

The protocol for Audio Transmit Server.



- ✓ Audio Port(Channel) can be connected only if it is 'LGS'
- ✓ Random Value in "CNS" response take 1 second to be created inside Camera

5-1. Connection Command

5-1-1. [CNS]

Command Definition: Response to Connection Request from client

- Request (Client -> Server) to connect to the server
- Response (Server -> Client) for the Connection Request

"STR"	P.S	CTR	"CNS"	NULL	"_END"
--------------	------------	------------	--------------	-------------	---------------

➤ "CNS" message is required before Authorization.

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'		'0'	'0'	'0'	'4'	'C'	'N'	'S'	0
'_'	'E'	'N'	'D'	0								

- Notify (Server -> Client)

➤ is not used in this command

- Notify Response (Client -> Server) for the Notify.

➤ is not used in this command

5-1-2. [LGN]

Command Definition: User Authentication (Request)

- Request

"STR"	P.S	CTR	"LGN"	RANDOM CONST	USER ID + PW	"_END"
--------------	------------	------------	--------------	---------------------	---------------------	---------------

➤ ID: 20byte,

➤ PW: 20byte

➤ RANDOM CONST : use RANDOM CONST parameter received from control connection

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'2'	'D'	'0'	'L'	'G'	'N'	0	RANDOM CONST (4Byte)
ID (20byte)								Password (20byte)						
'_'	'E'	'N'	'D'	0										

■ Response

➤ is not used in this command

■ Notify

➤ is not used in this command

■ Notify Response

➤ is not used in this command

5-1-3. [LGS], [LGW]**Command Definition: User Authentication Message(Response)**

■ Request

➤ is not used in this command

■ Response

"STR"	P.S	CTR	"LGS"	NULL	"_END"
-------	-----	-----	-------	------	--------

➤ Authentication Success Message.

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'0'	'L'	'G'	'S'	0	'_'	'E'	'N'	'D'	0
"STR"	P.S	CTR	"LGW"							NULL		"_END"						

➤ Authentication Failure Message

➤ Sample Code (Unit : Byte)

'S'	'T'	'R'	'T'	0	'0'	'0'	'0'	'4'	'0'	'L'	'G'	'W'	0	'_'	'E'	'N'	'D'	0
-----	-----	-----	-----	---	-----	-----	-----	-----	-----	-----	-----	-----	---	-----	-----	-----	-----	---

■ Notify

➤ is not used in this command

■ Notify Response ➤ is not used in this command

5-2. Transmit Stream Data**STREAM DATA**

➤

Structure of Stream Data**➤ Structure of Stream Data**

Type	Name	Description
------	------	-------------

unsigned char	start_code[5]	Start Code ("STRT")
unsigned char	packetsize[4]	Packet size
unsigned char	isStream	Packet Type ('1')
unsigned char	isCompMode	unuse
unsigned long	frame_num	frame number
unsigned long	frame_size	frame size
unsigned short	slice_num	Slice Number of Current Packet
unsigned short	slice_size	Slice Size of Current Packet
*unsigned char	channel_info	unuse
*unsigned char	resolution	unuse
*unsigned long	date_time	unuse
*unsigned short	frame_gop_num	unuse
*unsigned short	frame_type	unuse
unsigned char	frame_data[1400]	Payload (Stream Data)
unsigned char	end_code[5]	Ending Code ("END")


Appendix #1 details of Motion Area information

- The motion area information should be defined in the length of **72Bytes**.
- below information should be applicable with “Detect area map” in 2-2-5 [SDM,RSM] and “Motion Detection info” in 3-2 [Transmitting Stream Data]
- Motion area can be composed with **4Byte (cross) * 18Bytes(down)** which is total 72Bytes.
- 4Byte of cross information can process with “bit” basis, so it can include 32 of row information
- block number of motion are information will be depending to the video resolution. (refer below table)
- each motion block has a value of “0” or “1”
- when the value is “1”, it stands for the status of motion detection

[Motion area information as per respective resolution]

- The resolution of **1920 X 1080** will have motion size of **cross 20 blocks x down 20 blocks**
- One motion area block of 1920 X 1080 will have the size of **“96 x 67 pixel”**.

'1 byte								'1 byte								1 byte								1 byte								
1	2	3	4	5	6	7	8																									






-The resolution of **1280 X 720** will have motion size of **cross 16 blocks x down 9 blocks**

-One motion area block of 1280 X 720 will have the size of "**80 x 80 pixel**".


'1 byte'								' 1 byte'	1 byte	1 byte	
1	2	3	4	5	6	7	8				




- The resolution of **D1(4CIF)** will have motion size of **cross 9 blocks x down 6 blocks**

- One motion area block of 1280 X 720 will have the size of "**80 x 80 pixel**" (NTSC format)


'1 byte'								' 1 byte'	1 byte	1 byte	
1	2	3	4	5	6	7	8				






- The resolution of **CIF** will have motion size of **cross 4 blocks x down 3 blocks**
- One motion area block of 1280 X 720 will have the size of "**80 x 80 pixel**" (NTSC format)

'1 byte								' 1 byte		1 byte				1 byte			
1	2	3	4	5	6	7	8										



**[summary of motion size based on Resolution]**

Resolution	Block Count	Mount Type	Width(SD)-Pixel	Height(SD)-Pixel	Width(HD)-Pixel	Height(HD)-Pixel
1080i(1920*1080)	20*16				96	67
720p(1280*720)	16*9				80	80
D1(720*576)	9*6	PAL	80	96	80	96
4CIF(704*576)						
D1(720*480)	9*6	NTSC	80	80	80	80
4CIF(704*480)						
CIF(352*288)	4*3	PAL	88	96	88	96
CIF(352*240)	4*3	NTSC	88	80	88	80

Appendix #2 structure of UDP Multicasting message

-Below message structure is for the searching the IP camera in the network, this structure is the basis of PROBE IP searching program which is provided as default.

```
typedef struct __QUERY_TYPE__ {
    unsigned long query_flag;
    unsigned long reply_flag;
    unsigned long net_type;
    unsigned char product_type[24];
    unsigned char mac_addr[24];
    unsigned char ip_addr[4];
    unsigned char net_mask[4];
    unsigned char gw_addr[4];
    unsigned char dns[4];
    unsigned char web_port[2];
    unsigned char control_sock[2];
    unsigned char stream_sock[2];
    unsigned char vcrecv_sock[2];
    unsigned char vcsend_sock[2];
    unsigned char https[1];
    unsigned char reserved[47];
}PM_QUERY_TYPE, *PPM_QUERY_TYPE;
```

```
#define UDP_PORT_SEND 40011
#define UDP_PORT_READ 40012
#define PM_QUERY_FLAG 1L
#define PM_SETTING_FLAG 2L
```

[Send]

1. m_pSendSocket->Create(UDP_PORT_SEND, SOCK_DGRAM);
2. m_pSendSocket->SetSockOpt(SO_BROADCAST, &query_type, sizeof(PM_QUERY_TYPE));
3. m_pSendSocket->SendTo(&query_type, sizeof(PM_QUERY_TYPE), UDP_PORT_SEND, "255.255.255.255");

[Receive]

```
LONG CSearchTestDlg::OnReceive(WPARAM wParam, LPARAM lParam)
```

```

{
int flag;
PM_QUERY_TYPE recv_data;
unsigned int port;
CString addr;
flag = m_pSocket->ReceiveFrom(&recv_data, sizeof(PM_QUERY_TYPE), addr, port);
switch(flag)
{
case 0:
m_pSocket->Close();
AfxMessageBox("recevie error!!! [Clsoe Socket]");
break;
case SOCKET_ERROR:
m_pSocket->Close();
AfxMessageBox("recevie error!!! [Clsoe Socket]");
break;
default:
{
if(recv_data.query_flag == PM_QUERY_FLAG)
{
TRACE("PM_QUERY_FLAG\n");

m_ServerInfoList.AddTail(recv_data); // actual data to use
InsertItem(recv_data);
}
else if(recv_data.query_flag == PM_SETTING_FLAG)
{
}
}
break;
}

return 0L;
}

```

- ***End of Documentation-***